

Commercial Freezers DOE Test Report

Brand Name	Master Cook
Product	Commercial Freezer
Description	The product covered by this report is a commercial used, cord connected freezer
Model	IGV-2FF-HC
Ratings	AC 115V, 60 Hz, 1PH, 4.2 A
Date of receipt of sample	2021/01/20
Date of test	2021/01/21 – 2021/02/03
Test standard (s) or criteria (s)	10 CFR Part 431 Subpart C, 10 CFR 431.64, and 10 CFR Part 431.66 (e) ANSI/AHRI Standard 1200 (SI)-2013 ANSI/ASHRAE Estándar 72-2014
Conclusion	These results are in compliance with DOE requirement for commercial freezers


Prepared by: Zheng Guogen

Approved by: Huang Henglong

Signature:



Signature:



Product Information:

Model number or Unit Under Tested	IGV-2RR-HC
Defrost system*	Autommatic defrost
Product Group Code	6
Equipment Category	Self-Contained Commercial Refrigerators and Commercial Freezers With Doors
Equipment Family	Vertical Closed Solid (VCS)
Condensing Unit Configuration	Self Condensing
Multiple Compartments	No
Door	Solid
Number of Doors	2
Door Opening Orintation	Hinged
Refrigerant Type	R290
Rating Temperature (°F)	0

- Refrigerator coils are kept below the freezing point(32 degrees Fahrenheit). During compressor down-time, the evaporator starts to defrost. Run-off water is drained into the evaporator pan and evaporated. Freezer coils are defrosted electrically. Automatic defrost timers automatically initiate at pre-set intervals and for a pre-determined duration.

Critical Components:

Name	Manufacturer/trademark	Type/model	Technical data
Compressor	EMBRACO	EMC3134U	115VAC, 60Hz, R290

Test Condition:

Dry Bulb	72.5 $\pm$ 1.8 °F
Wet Bulb	64.4 $\pm$ 1.8 °F
Illumination	$\geq$ 800 lux
Input Voltage	115V
Input Frequency	60 Hz

Test Result:

Sample No.	Sample 1	Sample 2
Unit Test Voltage, Volts	115V	115V
Integrated Average Temperature of Product Simulators, °F	0.752	1.544
TDEC, kW h per day	4.734	4.747
Sampling size	2	
Mean of sample	4.741	
Sample standard deviation	0.009	
UCL/1.1	4.347	
Decided TDEC, kW h per day	4.741	

Exterior Dimension (W X D X H), in	28.9 x 32.2 x 82.5
Total Refrigerated Volumen, ft ³	21.48
Total Display Area, TDA, ft ²	NA
TDEC/Refrigerated Volumen, kW h/ft ³ per day	0.221
TDEC/Refrigerated Area, kW h/ft ² per day	NA
Rated DEC, kW h per day	NA
Maximun DEC for Doe, kW h per day	6.106
Comply with DOE requirement	Pass