

## PROJECT TITLE :

|                                                                                   |         |  |           |  |
|-----------------------------------------------------------------------------------|---------|--|-----------|--|
|  | Company |  | Client    |  |
|                                                                                   | Author  |  | File Name |  |

-----  
midas Gen - RC-Mesh Flexural Wall Design [ NSR-10 ] Gen 2025  
=====

=====

## -. Information of Parameters.

Elem No. : 1566  
LCB No. : 1  
Materials : fc = 27.5790 MPa.  
Fy = 413.6856 MPa.  
Thickness : t = 300.0000 mm.

## -. Design Forces.

Sig\_x = 0.0275 MPa.  
Sig\_y = -0.0884 MPa.  
Tau\_xy = -0.0363 MPa.  
  
Sig\_max = 0.0275 MPa. (x-dir)  
Sig\_min = -0.0884 MPa. (y-dir)  
Tau\_xy = -0.0363 MPa.

## -. Required Reinforcement and Concrete stress.

(Sig min in Tension or Sig max\*Sig min <= Tau xy^2 --> Rebar Required!)  
ft\_max = |Tau\_xy| - Sig\_max = 0.0088 MPa. (x-dir)  
ft\_min = |Tau\_xy| - Sig\_min = 0.1248 MPa. (y-dir)

f'tx = 0.0088 MPa.  
f'ty = 0.1248 MPa.  
Sig\_c = 2\*|Tau\_xy| = 0.0726 MPa.

rhoy\_req = 0.0015  
rhox\_req = 0.0025

## -. Tensile Strength provided by Reinforcement.

b = 1.0 mm. (by Unit Length).  
Asx\_Req = 0.7500 mm^2/mm. ( 750.0000 mm^2/m.)  
Asy\_Req = 0.4500 mm^2/mm. ( 450.0000 mm^2/m.)  
Asx\_use = 0.8000 mm^2/mm. ( 799.9984 mm^2/m.)  
Asy\_use = 0.5161 mm^2/mm. ( 516.1280 mm^2/m.)  
ftnx = Asx\_use/(b\*t)\*fy = 1.1032 MPa.  
ftny = Asy\_use/(b\*t)\*fy = 0.7117 MPa.

## -. Check the Ratio.

Rein. Bar\_x : (Hor.)  
Rein. Bar\_y : (Ver.)  
Rat\_x = f'tx/ftnx = 0.008  
Rat\_y = f'ty/ftny = 0.175  
Rat\_c = Sig\_c/fc = 0.003  
Rat = Rat\_y = 0.175 < 1.0 ---> O.K !